QUALITY OF SURFACE WATER

WALKER RIVER BASIN

Walker Lake is a perennial, natural terminal lake that became at-risk because of upstream agricultural diversions. Between 1882 and 1994, upstream diversions caused Walker Lake to decline about 140 feet and the total dissolved solids (TDS) concentrations to increase from 2,500 mg/L to 13,300 mg/L. The Lahontan cutthroat trout (LCT), a threatened species that is native to Walker Lake, has adapted to the high TDS of terminal basins. However, diversions have lowered lake levels and increased TDS to concentrations that threaten the survival of the LCT. The objectives of this project are to develop (1) an improved water budget for Walker Lake and (2) the capability to predict how changes in irrigation practices in and below Mason Valley will affect flows in the lower Walker River so alternatives for supplementing flows can be evaluated.

WATER-QUALITY DATA, WATER YEAR OCTOBER 2003 TO SEPTEMBER 2004

Station number			Station name						Date	Time	Sam	ple type	Instantaneous discharge, cfs (00061)
10293500 10300000 10301500	WEST	WALKER	RIVER AB RIVER NE NEAR WA	AR HUDS					03-08- 03-08- 03-08- 03-08-	04 0950 04 1430	Enviro	onmental onmental onmental	33 45 24
10301600											21		
10301720 10302002 10302005 10302025	WALKER RIVER AT PT SITE BELOW WEBER RESERVOIR NEAR SCHURZ, NV WALKER RIVER AT LATERAL 2-A SIPHON NEAR SCHURZ, NV WALKER RIVER AT POWERLINE CROSSING NEAR SCHURZ, NV WALKER RIVER NEAR MOUTH AT WALKER LAKE							03-08- V 03-09- 03-09- 03-09- 03-09-	04 0900 04 1130 04 1400	Enviro Enviro	onmental onmental onmental	2.6 .52 1.2 1.7	
Date	Baro- metric pres- sure, mm Hg (00025)	Dis- solved oxygen, mg/L (00300)	Dissolved oxygen, percent of saturation (00301)	pH, water, unfltrd field, std units (00400)	Specif. conduc- tance, wat unf uS/cm 25 degC (00095)	Temper- ature, air, deg C (00020)	Temper- ature, water, deg C (00010)	Calcium water, fltrd, mg/L (00915)	Magnes- ium, water, fltrd, mg/L (00925)	Potas- sium, water, fltrd, mg/L (00935)	Sodium, water, fltrd, mg/L (00930)	Alkalinity, wat flt inc tit field, mg/L as CaCO3 (39086)	Bicarbonate, wat flt incrm. titr., field, mg/L (00453)
03-08-04 03-08-04 03-08-04 03-08-04 03-08-04	652 652 657 659	10.5 10.3 8.5 9.1	113 93 107 101	7.4 7.5 7.5 7.4	350 503 484 455	18.0 14.0 	11.6 9.0 19.0 13.3	31.6 40.5 39.2 38.3 36.9	7.15 10.3 9.24 9.10 8.95	4.67 4.35 5.08 4.98 4.62	32.6 52.9 52.1 50.4 46.3	117 150 147 150	145 183 179 182
03-08-04 03-09-04 03-09-04 03-09-04	660 659 658 660	6.2 6.6 6.3 7.7	64 72 75 93	7.6 7.5 7.6 8.1	511 552 629 1,040	 	10.5 12.4 16.7 17.1	.02 36.6 46.5 55.0 42.8	<.008 8.17 11.3 14.1 12.8	<.16 4.99 5.81 8.69 11.7	<.10 62.8 59.1 61.4 168	190 191 209 271	232 233 255 338
			Date	Chloride, water, fltrd, mg/L (00940)	Fluoride, water, fltrd, mg/L (00950)	Silica, water, fltrd, mg/L (00955)	Sulfate water, fltrd, mg/L (00945)	Residue on evap. at 180degC wat flt mg/L (70300)	Iron, water, fltrd, ug/L (01046)	Mangan- ese, water, fltrd, ug/L (01056)			
			03-08-04 03-08-04 03-08-04 03-08-04 03-08-04	7.09 34.2 25.0 25.4 20.8	.5 .9 .8 .8	20.4 20.5 19.9 <i>19.6</i> 13.9	44.3 45.1 56.1 55.9 48.4	225 308 301 302 278	57 12 E5 <i>E4</i> 10	115 140 19.2 <i>18.5</i> 344			
			03-08-04 03-09-04 03-09-04 03-09-04 03-09-04	<.20 19.8 22.2 24.9 64.5	<.2 .8 .7 .6 1.9	<.04 25.6 14.6 32.1 31.2	<.2 44.1 53.2 77.7 152	<10 320 341 404 666	<6 E6 7 E6 20	.9 985 178 63.4 78.4			

Remark codes used in this table:

< -- Less than
E -- Estimated value